

Check inventory, process payments and capture data anywhere on the sales floor with the Motion[®] CL-Series SlateMate[™], an industryfirst integrated expansion solution that transforms the CL910 Tablet PC into a mobile-point-of-sale (MPOS) and data acquisition tool. The CL-Series SlateMate with Magnetic Stripe Reader (MSR) and Barcode Scanner (BCS) is securely integrated into the internal frame of the CL910, serving as a streamlined productivity solution that doesn't require connections to third party devices.

SlateMate for Retail

The CL910 with SlateMate is the ideal solution for retailers to improve customer satisfaction, increase workforce productivity and enhance data integrity. Serving as a MPOS terminal, the CL910 with MSR and BCS combines the ability to process payments, manage inventory status, or gain insight into customer details directly at the point of service.



The CL-Series SlateMate with MSR and BCS enables:

- Improved customer satisfaction and loyalty
- Enhanced store experience
- Empowered store associates and knowledgeable advisors
- Improved transaction times
- Reduced customer abandon rates
- Expanded transaction capabilities during peak periods
- Increased revenue per transaction

With the ability to read virtually all barcodes used by retailers, the CL-Series SlateMate offers seamless, reliable, fast and managed scanning. Additionally, because it uses MagTek® MSR technology, certified with most payment processors, the vast majority of retailers will be able to easily deploy the MSR in their environments. The CL-Series SlateMate with MSR and BCS provides the battery life, connectivity and PCI requirements retailers need to thrive in today's challenging business environments.

www.MotionComputing.com





$\textbf{Motion}^{\texttt{®}} \textbf{ CL-Series SlateMate}^{^{\text{\tiny M}}}$

With Magnetic Stripe Reader and Barcode Scanner

PRODUCT SPECIFICATIONS



Barcode Scanner	1D/2D Barcode Scanner Enabled Barcode Symbologies:	Dimensions	• L (332mm) H (180mm) W (15.4mm)
	Code 39, Code 128, UPC-A, UPC-E, Interleaved 2 of 5 MicroPDF417, PDF417, QR Code	Weight	• Weight = 135 g (.3 lb)
	Additional symbologies can be configured. Contact Motion for more information.	Durability	MIL-STD-810G, Method 516.6, Procedure IV (Transit Drop) IP52
Mag Stripe Reader	Reads 1, 2 & 3 Track Cards per ISO 7810 & 7811 and AAMVA	OS support	Genuine Windows [®] 7 Professional (32-bit)
		EMI, Safety, &	• ANSI C63.4
Mag Stripe Data	• TDES	Environmental	FCC Part 15B
Encryption Standards		Regulations	ICES-003 Class B
			CENELEC EN55022 Class B (CISPR 22)
Key Management Standards	• DUKPT		CENELEC EN 55024 (CISPR 24)
			AS/NZS 3548 Class B
			• 2002/95/EC (ROHS)
Expansion & Docking Compatibility	 Compatible with CL-Series Docking Station 		• 2002/96/EC (WEEE)
			 Art. 59.1 of Regulation 1907/2006 (SVHC) (REACH)
			Proposition 65
Buttons & Indicators	Barcode Scan button		 IEC 60950-1 2nd Edition (UL, CUL)
	Integrated beeper		EN 60950-1 2nd Edition (CE, Nemko, TUV)
	- Barcode Scan confirmation		
	• MSR LED	Specifications	 Operation Temperature: 0 ~ +43C
			 Storage Temperature: -10 ~ +60C
			 Humidity: 5% to 95% (Non Condensing)
			Mag Head operating life: 500K cycles Min.





www.MotionComputing.com